

MATERIAL SAFETY DATA SHEET

3010
01 00

MANUFACTURER'S NAME
MINWAX Company
10 Mountainview Road
Upper Saddle River, NJ 07458

EMERGENCY TELEPHONE NO.
(216) 566-2917

DATE OF PREPARATION
06-JAN-00

INFORMATION TELEPHONE NO.
(800) 523-9299

Section I -- PRODUCT IDENTIFICATION

PRODUCT NUMBER

HMIS CODES	
Health	2
Flammability	2
Reactivity	0

3010

PRODUCT NAME
MINWAX* Polyurethane Finish, Satin
PRODUCT CLASS
Polyurethane Coating

Section II -- HAZARDOUS INGREDIENTS

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	V.P.
Mineral Spirits. 64742-88-7	60	100	100	PPM	2.00
Amorphous Precipitated Silica 112926-00-8	1	10		6 MG/M3 as D	0.00

Section III -- PHYSICAL DATA

PRODUCT WEIGHT -- 7.20 lb./gal.	EVAPORATION RATE -- Slower than Ether
SPECIFIC GRAVITY -- 0.87	VAPOR DENSITY -- Heavier than Air
BOILING POINT -- 300-395 F	MELTING POINT -- N.A.
VOLATILE VOLUME -- 68 %	SOLUBILITY IN WATER -- N.A.
VOC (Theoretical) -- 4.35 lb.	522 gm. (less Federally Exempt Solvents)

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT 109 F PMCC	LEL 1.0	UEL 6.0
---------------------------	------------	------------

FLAMMABILITY CLASSIFICATION
Combustible, Flash above 99 and below 200 F

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Continued on page 2

=====

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

=====

Section V -- HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver and urinary systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

=====

Section VI -- REACTIVITY DATA

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

=====

Section VII -- SPILL OR LEAK PROCEDURES

Continued on page 3

=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

=====

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), 3 mg./m³ (respirable fraction), OSHA PEL 15 mg./m³ (total dust), 5 mg./m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

=====

Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY

2

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are COMBUSTIBLE. Keep away from heat and open flame.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====
Section X -- OTHER REGULATORY INFORMATION
=====-----
SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.